

# KEMPEROL LF

Once again, top KEMPEROL quality:  
Our construction product for the refurbishment  
of roof and building waterproofings

## Product benefits at a glance:



Solvent-free and  
virtually odourless



Single-component  
and ready to use



Can be used on almost  
all substrates without  
a primer



# Our new building product with proven **KEMPEROL** quality

With **KEMPEROL LF**, you get a single-component construction product which, in combination with **KEMPEROL Fleece**, is ideally suited for the repair and maintenance of roof and building waterproofings. The advantages of **KEMPEROL LF** are also and above all evident in complex detail work, because the material can be applied quickly and easily, even on difficult substrates.

## Processing

Simple and fast, leading to the usual perfect result

- 1** **KEMPEROL LF** is applied directly to the substrate. Depending on the substrate, the surface is pre-treated according to the primer recommendation.
- 2** The single-component material is applied directly from the container, using approximately 2/3 of the liquid construction product.
- 3** **KEMPEROL 165 Fleece** is rolled into the first **KEMPEROL LF** layer, overlapping by 5 cm, and worked in with a perlon roller to eliminate any bubbles.
- 4** Immediately afterwards, approximately 1/3 of the **KEMPEROL LF** waterproofing is applied wet-on-wet until the fleece is completely saturated.
- 5** After approximately 2 hours, the construction product will be rainproof. The fully adhesive **KEMPEROL LF** hardens to form jointless sealing that adapts to all substrate geometries and compensates for building movements. The fleece-reinforced sealing bridges cracks and is permanently elastic.

