

## KEMCO LE Flexo Adhesive Primer



### Application area

- Acts as an activator for KEMPEROL FALLSTOP in case of work interruptions > 7 d

### Features

- Lightfast
- Low viscosity
- Transparent
- Low consumption
- 1 part (single component)
- Ready for use
- Resin base: Polyurethane resin

### Container size:

1 l container

### Storage

Avoid direct sunlight and frost!

Store in closed original containers in dry rooms at temperatures between +5°C and +25°C.

To achieve the best results, it is recommended to store the product at room temperature for approx. 24 hours prior to use.

Opened containers must be sealed air tight and should be used as soon as possible.

See label for use before date.

### Material consumption:

at least 50 ml/m<sup>2</sup>

### Properties

Form	Liquid
Colour	Transparent
Cured after *	approx. 60 min.
Recoat after*	approx. 1 h to max. 6 h

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### Application

Substrates must be dry, firm and free from contaminants which may affect adhesion and must be prepared accordingly.

### Application

Use a cloth to apply the material thinly and evenly to the whole area of the substrate

Personal protective equipment must be worn.

Sufficient ventilation is essential to guarantee full curing. Always adhere to relevant rules and regulations.

For further information on application, please refer to the separate technical data sheets and the application instructions.

### Important note

Please refer to the respective safety data sheet for hazard warnings, protective measures, hazardous substance classes and correct disposal!

### Disposal

Liquid	EAK 08 05 01
cured	EAK 17 02 03

### GISCODE

PU50

### General information

The times given above are reduced with higher and increased with lower ambient and substrate temperatures. KEMPER SYSTEM products must not be mixed with other manufacturers' products.

Only for commercial use.

Our technical data sheets / technical information and our technical application advice only reflect the current state of knowledge in our company and our experience with our products. With each new edition, the previous technical information loses its validity. It is therefore essential that you always have the latest data sheet to hand. The latest version can be downloaded from [kemperol.de](http://kemperol.de) under Media > Downloads. When applying and using our products, a detailed, object-related, qualified check is required in each individual case to determine whether the respective product and/or the application technology meets the specific requirements and purposes. We are only liable for the freedom from defects of our products, but only if our respective product has been used and processed in accordance with our processing guidelines in the technical data sheets. The proper and professional processing of our products is therefore the sole responsibility and liability of the user (processor). Our products are sold exclusively on the basis of our terms and conditions of sale and delivery.

Issued: Vellmar, 2024-03-04