

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: **KEMPERDUR AC-Finish traffic grey B**
- UFI: AMQ9-70HM-P009-N884
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
 - Identified use: intended for professional use only!
- Application of the substance / the mixture: Sealing
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: KEMPER SYSTEM GmbH & Co. KG
Holländische Strasse 32-36
34246 Vellmar
Deutschland / Germany
Telefon: +49 (0)561 / 8295-0
Telefax: +49 (0)561 / 8295-5110
E-Mail: MSDS@KEMPER-SYSTEM.COM
- Further information obtainable from: research & development
- 1.4 Emergency telephone number: Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008
 - Flam. Liq. 2 H225 Highly flammable liquid and vapour.
 - Skin Irrit. 2 H315 Causes skin irritation.
 - Skin Sens. 1 H317 May cause an allergic skin reaction.
 - STOT SE 3 H335 May cause respiratory irritation.
 - Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- 2.2 Label elements

- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms



GHS02 GHS07 GHS09

- Signal word

Danger

- Hazard-determining components of labelling:

methyl methacrylate
2-ethylhexyl acrylate
Triethylene glycol dimethacrylate
2,2-bis(acryloyloxymethyl)butyl acrylate
Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
2-(2H-Benzotriazol-2-yl)-p-cresol
Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

- Hazard statements

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H411 Toxic to aquatic life with long lasting effects.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- 2.3 Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

- vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures

- Description: Mixture: consisting of the following components.

- Dangerous components:

CAS: 80-62-6 EINECS: 201-297-1	methyl methacrylate Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	25-50%
CAS: 103-11-7 EINECS: 203-080-7	2-ethylhexyl acrylate Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412	≥12.5-<20%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	2.5-10%
CAS: 64742-55-8 EINECS: 265-158-7	Distillates (petroleum), hydrotreated light paraffinic Asp. Tox. 1, H304	≥0.5-<2.5%
CAS: 1308-38-9 EINECS: 215-160-9	dichromium trioxide substance with a Community workplace exposure limit	0.5-2.5%
CAS: 109-16-0 EINECS: 203-652-6	Triethylene glycol dimethacrylate Skin Sens. 1, H317	≥1-<2.5%
CAS: 15625-89-5 EINECS: 239-701-3	2,2-bis(acryloyloxymethyl)butyl acrylate Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥1-<2.5%
CAS: 2440-22-4 EINECS: 219-470-5	2-(2H-Benzotriazol-2-yl)-p-cresol Aquatic Chronic 1, H410; Skin Sens. 1B, H317	≥1-<2.5%
CAS: 1065336-91-5 EC number: 915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate Repr. 2, H361f; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1A, H317	≥0.5-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures

- General information:

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down.

- After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

- After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints.

- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eye.

- After swallowing:

If symptoms persist consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media

- Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing agents:

Water with full jet

- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.
Nitrogen oxides (NO_x)

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 2)

- 5.3 Advice for firefighters
- Protective equipment:
- Additional information

Carbon monoxide (CO)

Do not inhale explosion gases or combustion gases.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

- Information about storage in one common storage facility:

Store away from foodstuffs.

- Further information about storage conditions:

Protect from frost.
Store in dry conditions.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C
3

- Storage class:

3

- 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

OEL	Short-term value: 100 ppm Long-term value: 50 ppm IOELV, Sens
-----	---

1308-38-9 dichromium trioxide

OEL	Long-term value: 2 mg/m ³ as Cr; IOELV
-----	--

- Regulatory information

OEL: 2021 CoP for the Safety, Health and Welfare at Work

- Additional information:

The lists valid during the making were used as basis.

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31



Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 3)

<p>- Respiratory protection:</p>	<p>When used properly and under normal conditions, breathing protection is not required. Use suitable respiratory protective device in case of insufficient ventilation. Filter A/P2 Respiratory protection - Gas filters and combination filters according to (DIN EN 141)</p>
<p>- Hand protection</p>	<div style="display: flex; align-items: center;">  <p>Protective gloves</p> </div> <p>Only use chemical-protective gloves with CE-labelling of category III. Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation After use of gloves apply skin-cleaning agents and skin cosmetics.</p>
<p>- Material of gloves</p>	<p>Recommended materials: Butyl rubber, BR Recommended thickness of the material: ≥ 0.5 mm Penetration time (min.): < 480 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.</p>
<p>- Penetration time of glove material</p>	<p>The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.</p>
<p>- As protection from splashes gloves made of the following materials are suitable:</p>	<p>Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.1 mm Penetration time (min.): < 10</p>
<p>- Eye/face protection</p>	<div style="display: flex; align-items: center;">  <p>Tightly sealed goggles</p> </div> <p>Protective goggles and facial protection - Classification according to EN 166</p>
<p>- Body protection:</p>	<p>protective clothing (EN 13034)</p>

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties	
- General Information	
- Colour:	According to product specification
- Odour:	Characteristic
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	100 °C
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	0.8 Vol %
- Upper:	12.5 Vol %
- Flash point:	10 °C
- Ignition temperature:	245 °C
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	1,200 mm ² /s
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.12 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 4)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**
- **VOC (EC)** 4.30 %
- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Highly flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** After the addition of catalysts, exothermic polymerisation might occur.
Reacts with peroxides.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

80-62-6 methyl methacrylate

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	29.8 mg/l (rat)

103-11-7 2-ethylhexyl acrylate

Oral	LD50	4,435 mg/kg (rat) (IUCLID)
Dermal	LD50	7,522 mg/kg (rabbit) (IUCLID)

1308-38-9 dichromium trioxide

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Inhalative	LC50/4 h	>5.41 mg/l (rat) (OECD 403)

109-16-0 Triethylene glycol dimethacrylate

Oral	LD50	10,066 mg/kg (rat)
Inhalative	LC50/4 h	>2,000 mg/l (mouse)

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

Oral	LD50	3,180-5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) 5,170 mg/kg (rabbit)

2440-22-4 2-(2H-Benzotriazol-2-yl)-p-cresol

Oral	LD50	>10,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	LC50/4 h	>403 mg/l (rat) (OECD 403)

1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

Oral	LD50	3,230 mg/kg (rat) (OECD-guideline 423)
Dermal	LD50	>3,170 mg/kg (rat) (OECD Guideline 402 (Acute Dermal Toxicity))

Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2'-[[2-(2-hydroxyethoxy)ethyl]-(4-methylphenyl)amino]-

Oral	LD50	619 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

- Endocrine disrupting properties

128-37-0 | 2,6-di-tert-butyl-p-cresol

List II

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

80-62-6 methyl methacrylate

NOEC	37 mg/l (Daphnia magna) (21 days; OECD 202 Part 2, flow)
EC3	37 mg/l (Scenedesmus quadricauda) (DIN 38412 Part 9; 8d)
EC0	100 mg/l (Pseudomonas putida)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: KEMPERDUR AC-Finish traffic grey B

(Contd. of page 6)

	EC50	69 mg/l (Daphnia magna) (48 h; OECD 202)
	LC 50	>79 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (96 h; OECD 203)
103-11-7 2-ethylhexyl acrylate		
Inhalative	LC50/8h	1.19 mg/l (rat) (OECD 403)
	LC50/96 h	1.8 mg/l (Oncorhynchus mykiss (Regenbogenforelle))
	EC50	17 mg/l (Daphnia magna) (48h; IUCLID)
	EC50	>10,000 mg/l (Pseudomonas putida) (30 min.; IUCLID)
	IC50	44 mg/l (DESMODESMUS SUBSPICATUS) (72h, IUCLID)
	LC50	23 mg/l (Leuciscus idus (Goldorfe)) (48h; IUCLID)
15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate		
	EC20	625 mg/l (Belebtschlamm) (30 min.; Methods ISO 8192)
	ErC50	4.86 mg/l (DESMODESMUS SUBSPICATUS) (OECD 201)
	EC50	18.8 mg/l /96 h (ALGAE)
		0.87 mg/l (fish) (OECD 203 (96 hr))
		19.9 mg/l (Daphnia magna) (OECD 202)
	ErC10	0.57 mg/l (DESMODESMUS SUBSPICATUS) (OECD 201)
	LC 50	1.47 mg/l (Leuciscus idus (Goldorfe)) (Methods DIN 38412 - part 15)
2440-22-4 2-(2H-Benzotriazol-2-yl)-p-cresol		
	LC50/96 h	>0.17 mg/l (Oncorhynchus mykiss (Regenbogenforelle)) (OECD 203)
	EC50	>1,000 mg/l (Daphnia magna) (24h; OECD 202)
1065336-91-5 Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate		
	EC50	0.42 mg/l (ALGAE) (OECD 201)
	LC50	0.9 mg/l /72 h (fish) (OECD 203 (96 hr))
Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]-(4-methylphenyl)amino]-		
	LC50/96 h	>100 mg/l (Cyprinus Carpio) (OECD 203 (96 hr))
	EC50	>100 mg/l (Scenedesmus subspicatus) (OECD 201; static)
	EC50	48 mg/l (Daphnia magna) (OECD 202; part 1 static)
	EC50	>100 mg/l (Cyprinus Carpio) (96h; OECD 203; ISO 7346; 92/69/CEE; C.1 static)
	NOEC	>100 mg/l (Scenedesmus subspicatus) (OECD 201, static)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:** Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal according to official regulations

- European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022






Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 7)

SECTION 14: Transport information

- 14.1 UN number or ID number - ADR, IMDG, IATA	UN1993
- 14.2 UN proper shipping name - ADR - IMDG - IATA	1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), ENVIRONMENTALLY HAZARDOUS FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED, 2,2-bis(acryloyloxymethyl)butyl acrylate), MARINE POLLUTANT FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED)
- 14.3 Transport hazard class(es) - ADR	<div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p style="margin-top: 10px;">- Class 3 (F1) Flammable liquids. - Label 3</p>
- IMDG	<div style="display: flex; justify-content: space-around; align-items: center;">   </div> <p style="margin-top: 10px;">- Class 3 Flammable liquids. - Label 3</p>
- IATA	<div style="display: flex; justify-content: space-around; align-items: center;">  </div> <p style="margin-top: 10px;">- Class 3 Flammable liquids. - Label 3</p>
- 14.4 Packing group - ADR, IMDG, IATA	II
- 14.5 Environmental hazards: - Marine pollutant: - Special marking (ADR):	Product contains environmentally hazardous substances: 2,2-bis(acryloyloxymethyl)butyl acrylate No Symbol (fish and tree) Symbol (fish and tree)
- 14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category	Warning: Flammable liquids. 33 F-E, S-E A
- 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
- Transport/Additional information: - ADR	----- Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- Transport category - Tunnel restriction code	2 D/E
- IMDG	----- Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: **KEMPERDUR AC-Finish traffic grey B**

(Contd. of page 8)

- UN "Model Regulation":

UN 1993 FLAMMABLE LIQUID, N.O.S. (METHYL METHACRYLATE MONOMER, STABILIZED), 3, II, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I

None of the ingredients is listed.

- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements

200 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements

500 t

- REGULATION (EC) No 1907/2006 ANNEX XVII

Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

H225 Highly flammable liquid and vapour.
 H302 Harmful if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H361f Suspected of damaging fertility.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS:

research & development

- Contact:

research & development

- Date of previous version:

27.07.2021

- Version number of previous version:

12

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2

(Contd. on page 10)

IE

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 17.10.2022

Version number 13 (replaces version 12)

Revision: 17.10.2022

Trade name: KEMPERDUR AC-Finish traffic grey B

(Contd. of page 9)

Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- **Sources**

- www.echa.europa.eu
- www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

IE