

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking




- **1.1 Product identifier**
- **Trade name:** **KEMPEROL V 210 Waterproofing (M) grey**
- **UFI:** VWW8-F0R9-F00R-4XEJ
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 - Identified use: intended for professional use only!
- **Application of the substance / the mixture** Waterproofing
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:** KEMPER SYSTEM GmbH & Co. KG
Holländische Strasse 32-36
34246 Vellmar
Deutschland / Germany
Telefon: +49 (0)561 / 8295-0
Telefax: +49 (0)561 / 8295-5110
E-Mail: MSDS@KEMPER-SYSTEM.COM
- **Further information obtainable from:** research & development
- **1.4 Emergency telephone number:** Medical Emergency information in case of poisoning:
Poison Information Center Mainz - 24 h - Phone: +49 (0) 6131 19240
(advisory service in German or English language)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 1	H372	Causes damage to the hearing organs through prolonged or repeated exposure.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
- **Hazard pictograms**

The product is classified and labelled according to the CLP regulation.

		
GHS02	GHS07	GHS08
- **Signal word** Danger
- **Hazard-determining components of labelling:** styrene
Phenol, methylstyrenated
maleic anhydride
Reaction mass of 2,2'-[[4-(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-
- **Hazard statements**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H361d	Suspected of damaging the unborn child.
H335	May cause respiratory irritation.
H372	Causes damage to the hearing organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
- **Precautionary statements**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 1)

- **Additional information:** EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

- Determination of endocrine-disrupting properties

68512-30-1	Phenol, methylstyrenated	List II
53306-54-0	Bis(2-propylheptyl)phthalat	List II

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture: consisting of the following components.

- Dangerous components:

CAS: 100-42-5 EINECS: 202-851-5	styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	0.5-2.5%
CAS: 68512-30-1 EINECS: 270-966-8	Phenol, methylstyrenated Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥1-<2.5%
CAS: 53306-54-0 EINECS: 258-469-4	Bis(2-propylheptyl)phthalat Substance identified as having endocrine disrupting properties (II)	0.5-2.5%
EC number: 911-490-9	Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl]-(4-methylphenyl)amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<0.5%
CAS: 108-31-6 EINECS: 203-571-6	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	≥0.001-<0.1%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
Do not leave affected persons unattended.
Personal protection for the First Aider.
Take affected persons out of danger area and lay down.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment in case of complaints.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
Protect unharmed eye.
If symptoms persist consult doctor.
- **After swallowing:**
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Use fire extinguishing methods suitable to surrounding conditions.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 2)

- 5.3 Advice for firefighters
- Protective equipment:
- Additional information

Nitrogen oxides (NOx)
Carbon monoxide (CO)

Do not inhale explosion gases or combustion gases.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.
Prevent from spreading (e.g. by damming-in or oil barriers).
Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents

- 6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities

- Storage:

- Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

- Information about storage in one common storage facility:

Store away from foodstuffs.

- Further information about storage conditions:

Protect from frost.
Store in dry conditions.
Keep container tightly sealed.
Recommended storage temperature: 5-30 °C

- Storage class:

3

- 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

100-42-5 styrene

OEL Short-term value: 170 mg/m³, 40 ppm
Long-term value: 85 mg/m³, 20 ppm

108-31-6 maleic anhydride

OEL Long-term value: 0.01 ppm
*Inhalable fraction and vapour, Sens

- Regulatory information

OEL: 2021 CoP for the Safety, Health and Welfare at Work

- 8.2 Exposure controls

- Appropriate engineering controls

No further data; see item 7.

- Individual protection measures, such as personal protective equipment

- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 3)

- Respiratory protection:

When used properly and under normal conditions, breathing protection is not required.
Use suitable respiratory protective device in case of insufficient ventilation.
Filter A/P2
Respiratory protection - Gas filters and combination filters according to (DIN EN 141)

- Hand protection



Protective gloves

Check protective gloves prior to each use for their proper condition.
Only use chemical-protective gloves with CE-labelling of category III.
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves

Recommended materials:
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.5 mm
Penetration time (min.): < 480
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

- Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

- As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.1 mm
Penetration time (min.): < 10

- Eye/face protection



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166 protective clothing (EN 13034)

- Body protection:

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Colour:	According to product specification
- Odour:	Like aromates
- Odour threshold:	Not determined.
- Melting point/freezing point:	Undetermined.
- Boiling point or initial boiling point and boiling range	Undetermined.
- Flammability	Not applicable.
- Lower and upper explosion limit	
- Lower:	Not determined.
- Upper:	Not determined.
- Flash point:	31 °C (DIN EN 22719)
- Decomposition temperature:	Not determined.
- pH	Not determined.
- Viscosity:	
- Kinematic viscosity at 20 °C	95 s (ISO 6 mm)
- Dynamic:	Not determined.
- Solubility	
- water:	Not miscible or difficult to mix.
- Partition coefficient n-octanol/water (log value)	Not determined.
- Density and/or relative density	
- Density at 20 °C:	1.16 g/cm ³
- Relative density	Not determined.
- Vapour density	Not determined.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 4)

- **9.2 Other information**
- **Appearance:**
- **Form:** Fluid
- **Important information on protection of health and environment, and on safety.**
- **Auto-ignition temperature:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- **Solvent separation test:**
- **VOC (EC)** 3.80 %
- **Change in condition**
- **Evaporation rate** Not determined.

- **Information with regard to physical hazard classes**
- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Flammable liquid and vapour.
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Danger of polymerisation.
Reacts with peroxides and other radical forming substances.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- LD/LC50 values relevant for classification:

100-42-5 styrene

Oral	LD50	5,000 mg/kg (rat)
	NOAEL	2,000 mg/kg (rat) (female) 1,000 mg/kg (rat) (male)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	NOAEC	0.21 mg/l (rat) (steam, female, 104 weeks)
	LOAEC	500 ppm (rat) (steam, male, 6 Hours)
	LC50/4 h	11.8 mg/l (rat)

68512-30-1 Phenol, methylstyrenated

Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

53306-54-0 Bis(2-propylheptyl)phthalat

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Oral	LD50	619 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)

108-31-6 maleic anhydride

Oral	LD50	400 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Suspected of damaging the unborn child.
- **STOT-single exposure** May cause respiratory irritation.
- **STOT-repeated exposure** Causes damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)** Repr. 2

- 11.2 Information on other hazards

- Endocrine disrupting properties

68512-30-1	Phenol, methylstyrenated	List II
53306-54-0	Bis(2-propylheptyl)phthalat	List II
80-54-6	2-(4-tert-Butylbenzyl)propionaldehyde	List II
115-86-6	triphenyl phosphate	List II

SECTION 12: Ecological information

- 12.1 Toxicity

- Aquatic toxicity:

100-42-5 styrene

NOEC	1.01 mg/kg (daphnia) (21 days, freshwater)
LC50	>1-<10 mg/l (Daphnia magna)
EC50	4.7 mg/l (daphnia) (48 hours, freshwater)
EC50	4.9 mg/l (ALGAE) (72 hours, freshwater)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 6)

EC50	>1-<10 mg/l (Daphnia magna)
LC50	10 mg/l (fish) (96 hours, freshwater) 4.02 mg/l (Pimephales promelas) (96h)
68512-30-1 Phenol, methylstyrenated	
ErC50	15 mg/l (daphnia) (OECD TG 201)
LC50/96 h	25.8 mg/l (daphnia) (OECD TG 203)
EC50	14-51 mg/l (daphnia) (OECD TG 202)
53306-54-0 Bis(2-propylheptyl)phthalat	
EC20	>1,000 mg/l (Belebtschlamm) (3h; DIN EN ISO 8192; OECD 209; 88/302/EWG; T.C aer)
NOEC	93.9 mg/kg (Chironomus riparius) (28d; OECD 218) 500 mg/kg (Eisenia fetida/foetida) (56d; OECD 222)
IC50	>20.5 mg/l (rat)
LC50/96 h	>10,000 mg/l (Brachydanio rerio (Ricefish)) (OECD 203; ISO7346; 84/449/EWG C.1 stat.)
EC50	>100 mg/l (Scenedesmus subspicatus) (72h; 88/302/EWG Part C, S.89 stat.)
NOEC	>10 mg/l (Brachydanio rerio (Zebraabrling)) (36d; OECD 210) >1 mg/l (Daphnia magna) (21d; OECD 202; part 2)
EC50	>100 mg/l (Daphnia magna) (48h; 79/831/EWG)
EC10	265 mg/kg (hu7) (28d; OECD 216)
NOEC	>1,000 mg/kg (Flowers) (OECD 208)
Reaction mass of 2,2'-[[4-methylphenyl]imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl][4-methylphenyl]amino]-	
LC50/96 h	>100 mg/l (Cyprinus Carpio) (OECD 203 (96 hr))
EC50	>100 mg/l (Scenedesmus subspicatus) (OECD 201; static)
EC50	48 mg/l (Daphnia magna) (OECD 202; part 1 static)
EC50	>100 mg/l (Cyprinus Carpio) (96h; OECD 203; ISO 7346; 92/69/CEE; C.1 static)
NOEC	>100 mg/l (Scenedesmus subspicatus) (OECD 201, static)
- 12.2 Persistence and degradability	No further relevant information available.
- 12.3 Bioaccumulative potential	No further relevant information available.
- 12.4 Mobility in soil	No further relevant information available.
- 12.5 Results of PBT and vPvB assessment	
- PBT:	Not applicable.
- vPvB:	Not applicable.
- 12.6 Endocrine disrupting properties	For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects	
- Additional ecological information:	
- General notes:	Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal according to official regulations

- European waste catalogue

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
15 01 10*	packaging containing residues of or contaminated by hazardous substances
17 02 03	plastic

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- 14.1 UN number or ID number
 - ADR, IMDG
 - IATA
 - 14.2 UN proper shipping name
 - ADR, IMDG
- | | |
|--|--------|
| | Void |
| | UN1866 |
| | Void |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31


Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: **KEMPEROL V 210 Waterproofing (M) grey**

(Contd. of page 7)

- IATA	RESIN SOLUTION
- 14.3 Transport hazard class(es)	
- ADR, ADN, IMDG	
- Class	Void
- IATA	
	
- Class	3 Flammable liquids.
- Label	3
- 14.4 Packing group	
- ADR, IMDG	Void
- IATA	III
- 14.5 Environmental hazards:	
- Marine pollutant:	No
- 14.6 Special precautions for user	Not applicable.
- 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
- Transport/Additional information:	
- ADR	
- Remarks:	Kein Gut der Kl. 3 gemäß 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code ADR / IMDG: Verpackung > 450 l = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VP III Außerhalb ADR / IMDG = UN 1866 - Kl. 3 - HARZLÖSUNG, entzündbar - VP III Not goods of cl. 3 in accordance with 2.2.3.1.5 ADR / 2.3.2.5 IMDG-Code ADR / IMDG: Packaging > 450 l = UN 1866 - cl. 3 - RESIN SOLUTION, flammable - PG III Outside ADR / IMDG = UN 1866 - cl. 3 - RESIN SOLUTION, flammable - PG III
- UN "Model Regulation":	Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148

- Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

- Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

- Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

- Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 03.08.2022

Version number 11 (replaces version 10)

Revision: 03.08.2022

Trade name: KEMPEROL V 210 Waterproofing (M) grey

- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

The safety data sheet issued is also compliant with the regulation Annex I of Regulation (EU) no. 453/2010 and Annex II of Regulation (EU) no. 2020/878.

- Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS:

research & development

- Contact:

research & development

- Date of previous version:

07.09.2021

- Version number of previous version:

10

- Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Corr. 1B: Skin corrosion/irritation – Category 1B
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Dam. 1: Serious eye damage/eye irritation – Category 1
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Resp. Sens. 1: Respiratory sensitisation – Category 1
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2
- Repr. 2: Reproductive toxicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- Asp. Tox. 1: Aspiration hazard – Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- Sources

- www.echa.europa.eu
- www.baua.de
- IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:
- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp
- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.