

## KEMPERTEC FALLSTOP Cleaner



### Uses

- Special cleaner for conventional PMMA, PC, PETG, GRP skylight domes

### Characteristics

- Low solvent content
- Ready-to-use
- Slightly volatile
- Cleans intensively and streak-free
- Based on an alcoholic solution

### Pack sizes

500 ml spray bottle

### Shelf Life

Can be stored cool, frost-free and dry.

### Usage guide

According to the level of soiling.

### Properties

Form	Liquid
Can be coated after*	approx. 15 min

\* Values obtained at a temperature of 23 °C - 50% rel. humidity. These values vary depending on the weather conditions, such as wind, humidity and temperature.

### Application

#### Preparing the substrate

The skylight domes to be coated must not be damaged (holes, cracks, etc.) and must be mounted on the roof in accordance with the manufacturers' installation guidelines. The processing instructions KEMPEROL FALLSTOP should be observed. KEMPERTEC FALLSTOP Cleaner spray evenly and thinly and rub with a clean cloth or brush. Avoid damaged places. Renew the wiping cloths several times. During the processing, personal protective equipment (PPE) should be worn, incl fall protection equipment according to BGR 198.

### Important notes

The safety data sheets, the labeling of the containers, the hazard warnings and the safety instructions on the containers must be observed during transport, storage and processing. The BG-Chemie data sheets must be observed during processing.

### Disposal

liquid EAK 08 04 09

### GISCODE

GGL10

### General information

Times are shortened in the case of higher and are longer in the case of lower ambient temperatures and subsurface temperatures. No substances of other systems may be mixed into the products of the KEMPER SYSTEM.

Only for commercial use.

Our technical data sheets / technical information and application instructions reflect the current level of knowledge in our company and the experience with our products. In each case, the new edition supersedes the previous technical information and renders it invalid. It is therefore necessary that you always have to hand the current code of practise. The latest version can be retrieved from the KEMPER SYSTEM Login section. When using our products, a detailed, object-related and qualified inspection is required in each individual case in order to determine whether the product and /or application technology in question meets the specific requirements and purposes. We are liable only for our products being free from faults, and this only if our relevant product has been used and applied according to the instructions in our technical data sheets. Correct application of our products therefore falls entirely within the scope of liability and responsibility of the user (contractor). Our products are sold exclusively on the bases of our conditions of sale and delivery.

Issued: Vellmar, 2023-03-30